vuegroup.org
sales@vue-cctv.co.uk



8 Channel DVR

Product code: VMC8PRO

8 Channel Digital Video Recorder. Connect up to 8 cameras for full 360° coverage of a vehicle or machine.

Video Input / Output	Up to 8 channels / A/V output connector CVBS (front), AHD (rear)
Audio Input / Output	Up to 8 channels / A/V output connection Analog Audio: rear panel
Video & Audio Codec	H.264 / G.711
Record Resolution	FHD (1920X1080), HD (1280X720), WD1 (960X480) D1 (720X480), HD1 (720X240), CIF (352X240)
Record FPS	1080p(FHD) 25 fps@8CH
Record Mode	Continuous, Event (G-sensor, Alarm, Motion), Dual (Continuous+event) SD Card dual recording
Local Playback	Video only, Calendar/Log Playback -4x, -2x, -1x, 1x, 2x, 4x, Pause, Step Playback
Alarm	Alarm-in(8EA): 4 (NC/NO), 4 (Signal) / Alarm-out(2EA): 2 (NC/NO)
LED	Power, SSD, Alarm, SD, OK, NG, LAN
Storage	2.5” SSD
LAN	10/100 Mbps
G-sensor/Gyro	X/Y/Z Axis
GPS (GNSS)	External GPS 1EA (GPS+GLONASS)

I/O External Port	· Serial: 2EA (Rear) (Expandable up to 6EA) [Port 0: Debug, EMS, Driver ID, IR Receiver, DT-STD, OBDII] [Port 1: EMS, Driver ID, IR Receiver, DT-STD, OBDII] · USB: 2EA (Rear) [Wifi, 3G Dongle, Memory Stick, US400] · Power: 5V/500mA x 2
Signal	Signal: LEFT, RIGHT, BRAKE, REVERSE, ACC Pulse: RPM, SPEED (2Hz, PullUp/PullDown)
Input	Front Panel: Arrow, SER, CH, ESC, MENU, FN, STA
Power	Input: DC 12/24V, 7A/4A / Output: DC 12V 2A
Language	English, Korean, Japanese, Chinese, Russian
Operating Temperature	-10 ℃ ~ 45 ℃ (SSD) / -10 ℃ ~ 60 ℃
Operating Humidity	0 ~ 90 %
Weight	970g (Unit) + 110g (SSD): 1.08Kg
Size	1DIN: 178mm(W) x 50mm(H) x 180mm(D)
Certificates	CE, E-mark, UKCA, FCC, KC